

**TYPES AVAILABLE:**    **DESCRIPTION:**

<b>GPO-01</b>	<b><u>General-purpose electrical</u></b> grade sheet meets or exceeds NEMA GPO-1.
<b>GPO-1P</b>	<b><u>General-purpose electrical punchable</u></b> grade sheet that ensures clean and fibre free cut edges.
<b>GPO-1P UV</b>	<b><u>General-purpose punchable sheet with UV</u></b> protection for exterior application
<b>MB 1100 FS</b> <i>U.L Recognized</i> <i>File No. E132409</i>	<b><u>UL Listed, General-purpose electrical</u></b> grade sheet, meets or exceeds NEMA GPO-1.
<b>1200 GPO-1,</b> <b>IEEE Class F</b> <i>155C/165C</i> <i>NEMA GPO-1</i>	<b><u>HIGH PERFORMANCE, LOW COST</u></b> upgraded general purpose electrical sheet often required in situations where performance is key and cost is an issue. Typically used in transformer spacers and supports.
<b>GPO-3</b> <b>GPO-3 Series</b> <i>U.L Recognized</i> <i>File No.E132409</i> <i>Class 180 &amp; 220</i>	High degree of flame retardancy and electrical insulating properties <b>4000</b> is a NEMA grade GPO-3 material with a ULV94V-0 fire rating for over 0.125”(1/8”) <b>4130</b> features improved weathering due to NPG/ISO/MMA resin system. <b>MB2200</b> is a GPO-3 material with a UL94V-0 fire rating for over 0.031”(1/32”)
<b>1030 HT</b> <i>U.L Recognized</i> <i>File No. E136182</i>	<b><u>HIGH TEMPERATURE</u></b> laminate for service temperatures in the <b><u>200°C to 220°C</u></b> Range, typically used in dry transformers
<b>1050 Wedge</b>	<b><u>HIGH TEMPERATURE and HIGH STRENGTH</u></b> laminate with excellent mechanical and electrical properties designed for use in motors.
<b>1050 ProTherm</b>	<b><u>HIGH TEMPERATURE</u></b> thermal insulation sheet is used as a thermal insulating board in the rubber moulding industry and can be sanded to tight tolerances when used as platen technology.
<b>1090 Semi-Conductive</b>	<b><u>SEMI-CONDUCTIVE</u></b> electrical grade laminate with excellent mechanical and electrical properties. Designed to provide a pathway for dissipating static charge and prevent flash over.

**STANDARD COLOURS:**

RED, WHITE, NATURAL, GREY (other colours available upon request).

**STANDARD SIZES:**

-36”x72”, 37”x73” and 48”x96” sheets, 1/32” - 6”, NEMA & plus NEMA Tolerances. All sheets are **HOMOGENEOUS** in thickness, **NO BONDING** or **JOINTS**

**CUSTOM SIZES:**

-Up to 60”x 118”, 1/32” up to 6”, NEMA & plus NEMA Tolerances.  
Metric thicknesses are also available.

**DELIVERY:**

-Stock for standard sheets, custom sizes as required.